



Applications

- Automotive Facilities
- Factories/Warehouses
- Boiler/Generating Rooms
- Water Treatment Facilities
- Wastewater Treatment Plants
- Chemical Processing
- Petrochemical Exploration
- Pulp & Paper Mills
- Pharmaceutical Labs
- Telecommunication Facilities
- Semiconductor Facilities
- Power/Cogeneration Plants

Benefits

- Economical Cost & Operation
- Industry Standard Output Signal
- Supports Several Gas Sensing Technologies
- No Programming or “Burn-In Time” Required
- Gas Specific Sensors equal No False Alarms
- Maintenance Free Operation
- Non-Intrusive Calibration Procedure
- Adjustment Free, One Person Calibration Procedure

Conspec's **CX Series** is an economical choice for toxic, combustible, and Oxygen gas monitoring. The CX Series is a simple and “smart” gas detector designed for use in hazardous or classified locations. An industry standard 4-20mA Analog output signal can be connected to any existing PLC, DCS, or EMS system. A simplified calibration procedure allows for a quick, non-intrusive, adjustment free calibration.

Installation time and costs are significantly reduced because all transmitters are shipped factory preprogrammed, calibrated, and tested on day of shipment. Installation cost can also be significantly reduced because the units can optionally be connected on a single 4-conductor cable via RS-485 instead of having to route individual cables to each unit.

Key Features

- Bright LED Status Indicators
- A Clear & Back-lit LCD Display
- Long Sensor Life
- Automatic Reset After Power Loss/Interruption
- Temperature & Humidity Compensated
- High Immunity to RFI &EMI
- One Year Limited Warranty

Specifications

Mechanical

Enclosure: Explosion Proof (UL Listed)

Enclosure Finish: Corrosion-Resistant, Polyester Powder Coated

Compliance: Class I Division 1 or 2
Groups B, C, & D
Class II, Groups E, F, & ,G
Class III

Weight: Approximately 3 Pounds

Conduit Entry: One (3/4" Cable Grip)

Environmental

Operating Temperature: -4°F to 140°F (-20°C to 60°C)

Temperature Compensation: Full Temperature Range

Operating Humidity: 10% to 95% RH Non-Condensing

Electrical

Operating Voltage: 12-24VDC

Cable Requirements: 3-Conductor 18 AWG Suggested

Current Consumption: 50mA Full Scale

Output Signal: Linear 4-20mA

System

Sensor Types: Electrochemical, Catalytic Bead, Infrared, Photo-Ionization, Thermal Conductivity

Programming: Via Optional Hand-Held IR Programmer

Modes: Two (Calibration & Normal)

Display: Two Line, *-Character Alphanumeric LCD Display

Status LED's: Green - Power; Yellow - Fan; Red - Alarm;
Red/Green - Sensor Fail

Total Alarms: Three (Alarm #1, Alarm #2, & Sensor Fail)

Alarm Set Point #1: User Defined

Alarm Set Point #2: User Defined

Available Options

- UP99 Hand-Held IR Programmer/Calibrator
- P9027 Enclosure Mounted Halogen Strobe
- P2063-3 Enclosure Mounted Piezo Horn
- P1643-2 Remote Alarm Unit
- P1879 Calibration Kit
- 900739 Relay Output Board
- P3000 Sample Pump

Ordering Information

• CXXX (Select Gas Below)

- 01-Ammonia
- 02-Carbon Dioxide
- 03-Carbon Monoxide
- 04-Chlorine
- 05-Combustibles
- 06-Hydrogen
- 07-Hydrogen Chloride
- 08-Hydrogen Sulfide
- 09-Nitric Oxide
- 10-Nitrogen Dioxide
- 11-Oxygen
- 12-Ozone
- 13-Sulfur Dioxide

****Other Gases Consult Factory

Sales Representatives & Distributors



CONSPEC®

CONSPEC Controls, Inc.

6 Guttman Blvd. • Charleroi, PA 15022
toll free: 1 (800) 487-8450 • fax: 1 (724) 489-9772
e-mail: sales.usa@conspec-controls.com
web site: www.conspec-controls.com